

AD-814



[Print](#)



Antenna Size:
0.866 x 0.866 in
[22 x 22 mm]

Electrical Characteristics

Operating Frequency
Integrated Circuit [IC] – Manufacturer & IC Name
RF Communications Protocol
Memory

Environmental

Operating Temperature
RoHS

Inlay Roll Format / Finishing

Un-wind direction
Core size with adaptor insert
Maximum roll outer diameter [not to exceed]

Part Details for AD-814(Total 2 Parts)

Part Number

Chip
Antenna dimensions, [CDxMD]
Die-cut dimensions
Inlay-to-liner adhesive
Liner material
Total thickness over chip [typical]
Standard pitch
Standard web widths
Inlay substrate material
Quality assurance
Average number of units per roll
Rev

Part Number

Chip
Antenna dimensions, [CDxMD]
Die-cut dimensions
Inlay-to-liner adhesive
Liner material
Total thickness over chip [typical]
Standard pitch
Standard web widths
Inlay substrate material

Features:

- Item-level tagging inlay optimized for edge-on performance
- Ideal for use on pharmaceutical bottles at FCC (US) frequencies. also very good on substrates like plastic and paper
- Maximum performance delivered for item level stacked arrays of goods
- Available in high yield / high capacity rolls which integrate seamlessly into high-volume converting processes

Market Applications: Supply Chain,Pharmaceutical / Heathcare

Global (860 - 960MHz)
Impinj Monza 3
ISO/IEC 18000-6C & EPCglobal Class 1 Gen 2
96 bits EPC

-40°F to 185°F [-40°C to 85°C]
Designed to comply with EU Directive 2002/95/EC

Inlay-side out
3 in [76.2 mm]
12 in [305 mm]

600196

Impinj Monza 3
0.866 [22 mm] x 0.866 [22 mm]
0.991 [25.18 mm] x 0.991 [25.18 mm]
E-828 (Fasson®)
40# SCK (Fasson®)
14 mils [356 um]
1.5 in [38.1 mm]
1.25 in [31.75mm]
N/A
100% edit and replace
7,500
00

600195

Impinj Monza 3
0.866 [22 mm] x 0.866 [22 mm]
N/A
N/A
N/A
11 mils [279 microns]
1.5 [38.1 mm]
1.596 [40.53]
PET

Quality assurance 100% read tested with out-of-tolerance inlay marked
Average number of units per roll 10,000
Rev 01

CARE AND HANDLING RFID inlays are sensitive to ESD. Observe standard practices to keep environment static charge to a minimum.

APPLICATIONS This product should be tested by the customer/user thoroughly under end use conditions to ensure the product is fit for any particular purpose or use.

WARRANTY Please refer to Avery Dennison RFID standard terms and conditions. The information contained herein is believed to be reliable but Avery Dennison makes no representation concerning the accuracy or correctness of the data.

PRODUCT CHANGES Avery Dennison RFID reserves the right to modify, change, supplement or discontinue product offerings at any time without notice.

TRADEMARK STATEMENT Avery Dennison, S490 and Fasson® are trademarks of Avery Dennison Corporation. For the most recent information on Avery Dennison products, visit www.rfid.averydennison.com.

Avery Dennison RFID

North America
866 903 RFID (7343)
Mexico +55 5093 0100
Europe +352 50 46 50 1
Asia Pacific +852 9163 1313
rfid.info@averydennison.com
www.rfid.averydennison.com



Hong Kong
Tel: 852-23702227
Fax: 852-23702054
sales@sysscan.com.hk

China & Hong Kong
Guangzhou
Tel: 86-20-87610063
Fax: 86-20-87610213
gz_sales@sysscan.com.hk

Shanghai
Tel: 86-21-62825319
Fax: 86-21-62825283
sh_sales@sysscan.com.hk

www.sysscan.com.hk or www.sysscan.com.cn