

IMAGETEAM™ 3900i Kit Series

USB Interface Fixed Position Linear Imager in Apple® iMac™ Frost Color



Features

Translucent Plastic Housing - Complements iMac computers and provides a sharp, modern look.

USB Interface - Compatible with iMac and other USB compliant PCs.

Bright, Sharp and Focused Aiming Line - Easy scanning by inexperienced users in any lighting condition.

100,000 Mean Time Between Failures and 5 Year Warranty - Long, reliable in-service life.

Powerful, Flexible Architecture - Connects and interfaces to all major PCs and Apple® computers. Windows®-based programming tools provided for easy setup and configuration.

Real World Reading Performance - Reads faded labels, short quiet zones, dot matrix printing, and printer-induced bar space variations.

HHP offers Frost colored scanners to complement the Apple® iMac™. The IMAGETEAM™(IT) 3900i is a fixed position linear imager that adds bar code scanning to kiosks and other OEM applications. The IT3900i uses linear imaging technology to deliver a bright, sharp aiming line, and fast reading and decoding that makes scanning intuitive and simple.

Bar code scanning at a kiosk is typically done by someone without scanning experience. The scan line must be easy to see. The scanner must read quickly, without perfect orientation, and read a wide variety of bar code labels. Since the bar code is presented to the scanner, the scanner must have a large working range. The IT3900i does all this and more. The IT3900i has an automatic trigger mode for constant scanning, or can be used in a presentation mode, where the scanner turns on when a bar code is placed in its viewing area. Scanning can also be controlled by the host computer via serial commands.

The IT3900i connects to the Apple iMac via the USB port. Kits include a USB cable.



IMAGETEAM™ 3900i Kit Series

Performance

Illumination:	630 NM Visible Red LED
Receiving Device:	3648 element linear imager
Reading Distance:	From 2.5 in. (6.35 cm) to 9 in. (22.8 cm) on medium density codes
Reading Width:	5 in. (12.7 cm) code width at 7 in. (17.8 cm) distance
Resolution:	3 mil. at 3.5 in. (8.8 cm) distance
Skew Angle:	±30°
Pitch Angle:	±15°
Horizontal Velocity:	2 in. (5.1 cm) per second
Minimum Reflectance Difference:	30%
Scan Rate:	Programmable to 270 scans per second
Decode Rate:	270 decodes per second

Mechanical/Electrical

Dimensions	
Length:	4.7 in. (11.9 cm)
Height:	1.5 in. (3.8 cm)
Width:	3.1 in. (7.9 cm)
Housing:	Polycarbonate/ABS blend, UL 940VO
Power Requirements:	5Vdc ± 10% at scanner
Current Draw:	<u>Scanning</u> <u>Standby</u>
@270 s/s	275mA 125mA
@67 s/s	150mA 125mA
Power Supply	
Noise Rejection:	Maximum 100mV peak to peak, 10 to 100 kHz
Triggering:	Continuous autotrigger mode, or via serial command
Mounting:	Three M-4 threaded inserts

Environmental

Temperature	
Operating:	+32°F to +122°F (0°C to +50°C)
Storage:	-40°F to 140°F (-40°C to +60°C)
Humidity:	0 to 95%
Mechanical Shock:	Operational after 5 drops from 5 ft. (1.53 m) to concrete
Ambient Illumination:	0 - 70,000 lux
ESD Protection:	Functional after 15kV discharge
Vibration:	Withstands 5G peak from 20 to 300 Hz
Agency:	FCC Class B, CE EMC Class B, CE Low Voltage Directive, EN60825-1 LED Safety: Class 1, UL, cUL listed, TÜV
MTBF:	per MIL-HDBK-217F Ground Benign exceeds 100,000 hours
Symbologies:	Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Postal Code, RSS.
Interfaces:	All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, Apple ADB, iMac, USB, TTL level RS-232, wand emulation mode, and includes (HHLC) non decoded laser compatible output.
Warranty:	Five year factory warranty.

MAGETEAM is a registered trademark of HHP.

iMac is a trademark of Apple Computer, Inc.

Apple is a registered trademark of Apple Computer, Inc.

Windows is a registered trademark of Microsoft Corporation in the United States and/or other countries.



Hong Kong Office : (852) 2370 2227
GuangZhou Office : 86-20-8759 1553
ShangHai Office : 86-21-6282 5319



Hong Kong
Tel: 852-23702227
Fax: 852-23702054
sales@sysscan.com.hk

China & Hong Kong
Guangzhou
Tel: 86-20-87591553
Fax: 86-20-87598472
gz_sales@sysscan.com.hk

Shanghai
Tel: 86-21-62825319
Fax: 86-21-62825283
sh_sales@sysscan.com.hk

www.sysscan.com.hk or www.sysscan.com.cn

