



## IT4200

### General Purpose 2D Area Imager



#### Hong Kong Main Office

Unit 1001, 10/F., Tower II, Cheung Sha Wan Plaza,  
833 Cheung Sha Wan Rd, Kln, Hong Kong. (Lai Chi Kok MTR Exit A)  
九龍長沙灣道833號長沙灣廣場二期十樓1001室 (荔枝角地鐵站A出口)  
Tel: (852) 2370 2227 Fax: (852) 2370 2054

#### Guangzhou Office

廣州市黃埔大道西275號  
摩托羅拉大廈玉蘭閣16B室  
Tel: 86-20-85517503 Fax: 86-20-87598472

#### Shanghai Office

上海延安西路1228弄2號  
嘉利大廈5H, ZIP: 200052  
Tel: 86-21-62825319 Fax: 86-21-62825283

### Features

*Ergonomic Design - Linear imager performance, with the versatility of area imaging all in a small, sleek housing.*

*Omni-directional reading of 1D, PDF417, MicroPDF417, Postal, Matrix, and EAN•UCC Composite codes, and OCR fonts for the easiest ever data collection.*

*Image Capture - Class-leading image quality and image transfer speed provide crisp images in less than one second.*

*Connectivity – The most popular interfaces in one model. Uses the standard Hand Held Products cable set.*

*Intelligent Aiming Options - Distinctive green aimer provides superior illumination contrast and makes image capture applications fast and intuitive.*

The IT4200 area imager from Hand Held Products combines the versatility of area imaging with the speed and cost of linear scanning for retail and commercial applications. Powered by Adaptus™ Imaging Technology, the IT4200 is full featured, fast, and cost effective.

Current and future manufacturing, retail, and commercial applications will involve much more than linear bar codes. EAN•UCC composite codes are beginning to appear in food stores, PDF codes are used for age verification in restricted item sales, and postal bar codes are used to sort mail. The omni-directional reading capability of the IT4200 allows fast and easy reading of all these codes. Simply point and shoot. There's no need to align a scan line, or wait for a raster beam to open up.

Whether capturing a signature as proof of delivery, taking a picture for identification, or electronic data storage, image capture is an important part of current and future solutions. The Adaptus Imaging Technology powered IT4200 is equipped with Hand Held Products fifth generation imaging for best-in-class image quality and image transfer speed, all at very economical prices. Image capture has become a mainstream application requirement. Trust Hand Held Products to provide the industry's best imaging.

With no moving parts, the IT4200 is as durable as it is versatile. Hand Held Products has a reputation for products that are tough as nails. The IT4200 is no exception, and will provide years of service at a low cost.

To learn how the IT4200 can work for you, contact us at any of the locations listed on the back or visit us at [www.handheld.com](http://www.handheld.com).

## Performance

### Aiming:

Green Aiming LED: 526nm ±30nm

### Image:

752x480. Binary, TIFF, or JPEG output.

### Working Range:

| IT4200 SR | 8.3 mil Linear<br>(.021cm) | 13 mil UPC<br>(.033cm) | 6.6 mil PDF417<br>(.017cm) | 10 mil PDF417<br>(.025cm)   | 15 mil Data Matrix<br>(.038cm)  | 35 mil MaxiCode<br>(.089cm) |
|-----------|----------------------------|------------------------|----------------------------|-----------------------------|---------------------------------|-----------------------------|
| Near      | 3.5 in. (8.9cm)            | 2.1 in. (5.3cm)        | 4.4 in. (11.2cm)           | 3.1 in. (7.9cm)             | 2.3 in. (5.8cm)                 | 2.0 in. (5.1cm)             |
| Far       | 7.5 in. (19.1cm)           | 13.1 in. (33.3cm)      | 6.1 in. (15.5cm)           | 8.9 in. (22.6cm)            | 10.1 in. (25.7cm)               | 12.9 in. (32.8cm)           |
| IT4200 SF | 7.5 mil Linear<br>(.019cm) | 13 mil UPC<br>(.033cm) | 6.6 mil PDF417<br>(.017cm) | 10 mil PDF417<br>(.025cm)   | 15 mil Data Matrix<br>(.038cm)  | 15 mil QR Code<br>(.038cm)  |
| Near      | 2.5 in. (6.4cm)            | 2.0 in. (5.1cm)        | 2.8 in. (7.1cm)            | 2.2 in. (5.6cm)             | 1.8 in. (4.6cm)                 | 2.2 in. (5.6cm)             |
| Far       | 6.4 in. (16.3cm)           | 8.8 in. (22.4cm)       | 5.9 in. (15.0cm)           | 7.5 in. (19.1cm)            | 7.4 in. (18.8cm)                | 7.1 in. (18.0cm)            |
| IT4200 HD |                            | 13 mil UPC<br>(.033cm) | 6.6 mil PDF417<br>(.017cm) | 35 mil MaxiCode<br>(.069cm) | 8.3 mil Data Matrix<br>(.021cm) | 10 mil QR Code<br>(.025cm)  |
| Near      |                            | 2.1 in. (5.3cm)        | 2.1 in. (5.3cm)            | 2.0 in. (5.1cm)             | 2.6 in. (6.6cm)                 | 2.2 in. (5.6cm)             |
| Far       |                            | 6.6 in. (16.8cm)       | 4.9 in. (12.4cm)           | 7.8 in. (19.8cm)            | 4.6 in. (11.7cm)                | 5.2 in. (13.2cm)            |

### Skew Angle:

±40°

### Pitch Angle:

±40°

### Horizontal Velocity:

4 in. (10 cm) per second

## Mechanical/Electrical

### Dimensions

Length: 5.5 in. (14.0 cm)

Height: 5.3 in. (13.5 cm)

Width: 2.6 in. (6.6 cm)

Weight: 4.5 oz. (127.6 g)

### Housing:

UL 94V0 grade

### Power Requirements:

5Vdc ±10% at scanner

### Current Draw (Typical)

| Input | Scanning | Idle  |
|-------|----------|-------|
| 5 V   | 382 mA   | 53 mA |

## Power Supply

### Noise Rejection:

Maximum 100mV peak to peak, 10 to 100 kHz

## Environmental

### Temperature

Operating: +32°F to +122°F (0°C to +50°C)

Storage: -40°F to 140°F (-40°C to +60°C)

### Humidity:

0 to 95%, non-condensing

### Mechanical Shock:

Operational after 25 drops from 4.9 ft. (1.5 m) to concrete

### Ambient Light:

Up to 100,000 lux (full sunlight)

### ESD Protection:

Functional after 100 8kV discharges

### Vibration:

Withstands 1G peak from 8 to 80 Hz

### Agency:

FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, C-Tick N10410

### MTBF:

per MIL-HDBK-217F Ground Benign exceeds 70,000 hours

## Symbologies

2 Dimensional: PDF417, MicroPDF417, MaxiCode, Data Matrix, QR Code, Aztec, Code 49, and EAN•UCC Composite

Linear: Codabar, Code 39, Interleaved 2 of 5, Code 93, Code 128, UPC, EAN, RSS, Codablock, and BC412\*  
\*available to licensed users

Postal: Postnet, Planet Code, British Post, Canadian Post, Japanese Post, KIX (Netherlands Post)

OCR Fonts: OCR-A, OCR-B

### Interfaces:

All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, USB, TTL level RS-232, wand emulation mode, TTL level Serial Wedge.

### Warranty:

Two year factory warranty.

## Hong Kong Main Office

Unit 1001, 10/F., Tower II, Cheung Sha Wan Plaza,  
833 Cheung Sha Wan Rd, Kln, Hong Kong. (Lai Chi Kok MTR Exit A)  
九龍長沙灣道833號長沙灣廣場二期十樓1001室 (荔枝角地鐵站A出口)  
Tel: (852) 2370 2227 Fax: (852) 2370 2054

## Guangzhou Office

廣州市黃埔大道西275號  
摩托羅拉大廈玉蘭閣16B室  
Tel: 86-20-85517503 Fax: 86-20-87598472

## Shanghai Office

上海延安西路1228弄2號  
嘉利大廈5H, ZIP: 200052  
Tel: 86-21-62825319 Fax: 86-21-62825283

## China & Hong Kong

**Hong Kong**  
Tel: 852-23702227  
Fax: 852-23702054  
sales@sysscan.com.hk

**Guangzhou**  
Tel: 86-20-87591553  
Fax: 86-20-87598472  
gz\_sales@sysscan.com.hk

**Shanghai**  
Tel: 86-21-62825319  
Fax: 86-21-62825283  
sh\_sales@sysscan.com.hk

[www.sysscan.com.hk](http://www.sysscan.com.hk) or [www.sysscan.com.cn](http://www.sysscan.com.cn)