

Product Profile

- An intelligent reader capable of hosting applications
- Software configurable to read and write EPC Gen 2 and ISO tags
- Operates in ETSI 865-868 MHz, or FCC 902-928MHz
- Monitors and controls presence detectors and signal lights
- Built in Java Script workbench for rapid application development
- Deployment services
- Ethernet and WiFi
- Built in device management
- Internal power supply



IF5 FIXED READER

Joining an already diversified line of RFID readers, the Intermec IF5 is a fixed “smart” reader that filters information from tags, monitors external sensors and controls audible/visual indicators, without the expense, and potential point of failure of a separate server “box”, required by other RFID scanning solutions. As with all Intermec reader products, the IF5 both reads and writes to RFID tags.

Filtering Information

Filtering incoming tag data means sending only pertinent information upstream to the host. The IF5 filters, manages and acts upon the data read from tags according to application parameters, all made possible by internal Java or Java Script applications. The Java application can also be programmed to change the configuration parameters of the IF5 in response to new incoming data from a tag or peripheral device. For example, a dock door portal – mounted IF5 reader can be programmed to scan the “destination” field on all tags passing through, and subsequently flash a red beacon light for the fork lift driver if an item is about to be incorrectly loaded.

Monitor Sensors/Visual Indicators

The IF5 reader includes powered general purpose input/output (GPIO) circuitry, which allows direct monitoring and/or controlling of peripherals such as presence detectors and signal lights without requiring extra devices and power supplies to facilitate the connection.

Development and Device Management

For rapid application development, Intermec provides development libraries for .Net and Java on Microsoft operation systems. Developers simply write the application once and have the capability to port it over to different RFID devices such as Intermec mobile and vehicle mount computers. Intermec SmartSystem Foundation, a remote management system, comes standard on the IF5. An intuitive administrator’s console provides centralized access to remote devices like the IF5 reader. Administrators can change device settings, send OS upgrades, update software applications, and execute other changes directly from the console to save time and significantly cut costs.

Ethernet and WiFi

The IF5 comes standard with an internal auto-range power supply, IPv4 and IPv6 plus an optional 802.11b/g CCX certified radio enabling seamless integration into existing Ethernet or WiFi infrastructures. The IF5 is straightforward to integrate and capable of continuous operation anywhere in the world.

Deployment Services

Ensure success with your RFID system by utilizing Intermec’s deployment services. Intermec’s deployment services can assist in initial process analysis and site analysis to full site installations.

Physical Characteristics**Length:** 35.6 cm (14 in.)**Width:** 23.1 cm (9.1 in.)**Height:** 9.53 cm (3.75 in.)**Environment****Operating Temperature:** -25°C to 55°C (-13° F to 131° F)**Storage Temperature:** -30°C to 75°C (-22° F to 167° F)**Humidity:** 10% to 90% (Non-condensing)**Enclosure:** IP53**Standard Features****Communications Interface options:**

Ethernet 10/100BaseT or Wireless 802.11g

Configuration: Internal web Graphical User Interface (GUI)**Input/Output Circuits:** Four input (0-40VDC) and four output (0-48VDC .5 amp) circuits, 500ma 12VDC power**Antenna Connections**

Four - Reverse SMA, -20dB software controlled

Power

110-240 VAC auto ranging

Power supply is internal and included

Duty Cycle: 100%**RFID Frequency Ranges**

ETSI 865-868 MHz, or FCC 902-928MHz

Tag Air Interfaces

Intellitag G1 (Fairchild G1)

ISO 18000-6b (Philips i-code HSL)

Philips Version 1.19

EPCglobal UHF Gen 2

Protocols

ANSI INCITS 256:2001

Intermec Basic Reader Interface

Connection to Network

Ethernet, 802.3 wired and optional 802.11g

Software

- IP v6
- SAMBA Client
- NFS Client
- BusyBox
- Telnet Server
- Syslog Client
- FTP Server
- PCMCIA Card Services
- OpenSSL
- J2ME/CDC
- Service Management Framework
- SAP-Auto ID Infrastructure (All)
- Intermec Network Apps
- HTTP/HTTPS Web Server
- TFTP Client
- DHCP Client
- DNS Client
- SNTP Client
- 802.1x Supplicant (used with 802.11)
- Intermec Developer Library
- Intermec Data Collection Engine
- Optional WebSphere Everyplace Device Manager (IBM)
- Optional J2SE (SUN)
- Java Virtual Machine
- Java Script Interpreter

Device Management

- SNMP
- Intermec SmartSystems client
- Wavelink Avalanche Client

Development

Built in Java and Java Script, Intermec Development Libraries for Java and .Net

Memory

32 Mbytes of SDRAM, 16 Mbytes Flash

Accessories

802.11g radio, antennas, antenna cables, mounting bracket, Compact Flash card

Standards

AIAG B-11

ANS INCITS 256:1999 (R2001) - Parts 2, 3.1 & 4.2

ANSI MH10.8.4

ISO/IEC CD18000 Part 4

ISO/IEC WD18000 Part 6

Part Number

IF5UC20380400004 - RFID Reader, Fixed, EPC global Gen 2 only, FCC, Ethernet (this is one of multiple unique configurations)

Restrictions On Use

Some approvals and features may vary by country and may change without notice. Please check with your local Intermec sales office for further information.

Disclaimer

Intermec reserves the right to make changes without notice to any products herein for any reason at any time, including but not limited to improving the reliability, form, fit, function or design. Please contact Intermec for current price list and availability.




Hong Kong
Tel: 852-23702227
Fax: 852-23702054
sales@sysscan.com.hk

China & Hong Kong
Guangzhou
Tel: 86-20-87591553
Fax: 86-20-87598472
gz_sales@sysscan.com.hk

Shanghai
Tel: 86-21-62825319
Fax: 86-21-62825283
sh_sales@sysscan.com.hk

www.sysscan.com.hk or www.sysscan.com.cn

