

**Intermec**

## Product Profile



- High performance print engine for demanding print and apply applications
- Increases productivity and label placement accuracy
- RFID Ready
- Easily adapts to changing host environments and applications
- Flexible and ample connectivity options
- Interchangeable print head provides choice of resolutions

### PA30 APPLICATOR PRINT ENGINE

Intermec's PA30 Print Engine is a rugged, reliable, metal, high performance applicator print engine designed to increase label placement accuracy and productivity in demanding 24/7 print and apply applications. The Intermec PA30 is easily upgradeable to RFID with Intermec's IM4 RFID reader module.

With its extra input/output receptacle (I/O), the PA30 can execute user-defined programs thereby eliminating the need for a PC. Flexible connectivity enables the use of up to seven wired and wireless interfaces simultaneously allowing the PA30 to issue commands to production line machinery, conveyors, and other printers, as well as access information directly from the network host.

The Intermec PA30 is fully programmable is not restricted by printer command language. It delivers investment protection by easily adapting to changing host environments and applications.

The PA30 can communicate with and replace competitive print engines without changes to host programming or label format design, providing additional functionality and continued investment protection.

The combination of powerful individually controlled micro-step motors, high capacity power supply and sophisticated thermal management print head ensures high-quality labels each and every time at up to 12 inches (30.5 cm) per second (first to last label).

Based on PX printer technology, proven technology used in variety of custom made applicators, the PA30 features 4-inch (10 cm) print width with left hand orientation and the same 5-bolt pattern used in other OEM Print Engine products. The PA30 is available with interchangeable 203 or 300 dpi resolution print heads.



# Intermec

**Application**

Direct Thermal (DT) and Thermal Transfer (TT) print and apply

**Physical Characteristic**

9 5/8" W x 11 7/8" H x 20 1/2" L

Weight: 29.8 lbs

**Print Specifications**

**Max. Print Width:** (DT) 4.4 in (112mm)/ (TT) 4.3 in (110mm)

**Max.Length with extended memory:**

161 in (4095 mm) at 203 dpi

109 in (2775 mm) at 300 dpi

**Print Speed:** 4-12 ips (50-300 mm/s) variable

**Print Direction:**

Prints smooth text, any size bar codes and graphics in all four orthogonal directions.

**Print Resolution:**

203 dpi (8 dots/mm), 300 dpi (11.8 dots/mm)

**Label/Ticket/Tag**

**Max. Width:** 4.72 in (120 mm)

**Min. Width:** 2.00 in (50.8 mm)

**Thickness:** 2.4 to 10 mil (60 to 250 µm)

**Style:** Roll-fed, die-cut, continuous or fanfold labels, tags or tickets based on the applicator design.

**Label Roll max diameter:** Based on the applicator design

**Label Roll Core:** Based on the applicator design

**Media Type:** Thermally sensitive media

**Ribbon Roll**

**Ribbon Roll max diameter:** 3.25 in (82.5 mm)

**Ribbon Roll Core:** 1.0 in (25 mm)

**Ribbon Type:** Wax, wax/resin, resin

**Interfaces**

**Standard:**

- Applicator Interface
- RS232, up to 115.2 kb/s
- USB 2.0
- EasyLAN 10/100BaseT internal Ethernet

**Optional:**

- EasyLAN Wireless Internal Ethernet

**Optional interfaces available as accessories:**

- Parallel IEEE 1284
- Industrial Interface (8 digital in/out, 4 analog relays, 1 RS232/422/485 port)\*
- Dual Serial ports RS-232, RS-422, RS-485 and 20mA Current Loop\*

**Network**

**EasyLAN integrated Ethernet:** RJ-45 connector for 10BaseT or 100BaseTX

**EasyLAN Wireless:** Fully integrated IEEE 802.11b/g; WEP 128 bit; 802.1x (EAP-TTLS, LEAP, PEAP and WPA-PSK authentication)

**Supported protocols:** TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP

**Note:** SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

**Software**

**Available printer command languages:**

- Fingerprint
- IPL (Future versions)

**Applications/Drivers (comes on Printer Companion CD) including:**

- InterDriver™ Windows printer driver
- Intermec ActiveX® Controls
- Intermec LabelShop® START label design & print package
- PrintSet for printer setup/configuration
- SmartSystem client for monitoring of network devices

**Note:** EasyCoder PX4i drivers can also be used

**Optional software for application development:**

- Fingerprint ApplicationBuilder™ (IFAB)
- ERPLabel™ for SAP™ R/3®
- XMLLabel™

**Bar Code Symbolologies**

**1-dimensional Codes:** Codabar, Code 11, Code 39, Code 93, MSI (modified Plessey), Code 128, Code 128 Subset A-C, DUN-14/16, UPC/EAN Codes (EAN 8, EAN 13, UPC Version A, UPC Version E), EAN-128, EAN-128 Subset A-C\*, Industrial 2 of 5, Interleaved 2 of 5, Interleaved 2 of 5 A, Matrix 2 of 5\*, Planet, Postnet, Straight 2 of 5\*, UCC-128 SSCC, RSS, HIBC Code 39 (IPL Only), HIBC Code 128 (IPL Only), JIS-ITF (IPL Only)

**2-dimensional Codes:** Aztec, Code 16K, Code 49, DataMatrix, Maxi Code, PDF 417, QR Code, MicroPDF417, EAN.UCC Composite

**Standards Supported:** UPC/EAN Shipping

Container; UCC/EAN 128 SSC, MH 10.8

Shipping Label; AIAG (shipping parts label);

LOGMARS; POSTNET; HIBCC: ISBT 128; GM1724;

UPS shipping label; Global Transport label

**Characters Sets**

**Fingerprint/DP Firmware:** 15 scalable fonts including 12 Unicode (1 WGL4), 1 symbol, 1 OCR-A, 1 OCR-B. Font cache for maximum performance. ATF font support. Non-Latin fonts are available as options.

**IPL firmware:** (Future versions) 13 scalable fonts + 20 bitmap fonts

**Graphics**

Supports PCX file format

**Memory**

**Standard:** 4MB FLASH, 16MB SDRAM

**Max.Option:** 16MB FLASH, 16MB SDRAM

**Maximum Compact Flash:** Utilize up to 1GB

**Protocol**

**Fingerprint/Direct Protocol:** XON/XOF, ENQ/ACK, DTR, RTS/CTS

**IPL (Future):** XON/XOF, Intermec Standard Protocol

**Display**

Back-lit LCD for 2X16 characters and 3 LED indicator lamps

**Keypad Control Panel**

- Advanced Keypad (Fingerprint/DP)
- Alpha-numeric keypad (FP/DP option)
- Simplified Keypad (Future IPL)

**Power Supply**

115/230VAC auto switch w/PFC; Voltage Range: 90-265 VAC; Frequency Range: 45-65 Hz

**Operating environment**

**Temperature:** +5° to +40°C (+40° to +104°F)

**Humidity:** 10-90% RH non-condensing

**Regulatory Approvals**

FCC, UL, CE

**Options**

Compact Flash Memory, FLASH and SDRAM SIMM, Various International Double Byte fonts, Alphanumeric keyboard/Keypad, Various Interface boards, RTC

**North America**

**Corporate Headquarters**  
6001 36<sup>th</sup> Avenue West  
Everett, Washington 98203  
tel: 425.348.2600  
fax: 425.355.9551

550 2nd Street S.E.  
Cedar Rapids, Iowa 52401  
tel: 319.369.3100  
fax: 319.369.3453

**Media Supplies**  
9290 Le Saint Drive  
Fairfield, Ohio 45014  
tel: 513.874.5882  
fax: 513.874.8487

**Europe/  
Middle East & Africa  
Headquarters**

Reading International Business Park  
Basingstoke Road  
Reading RG2 6DD  
United Kingdom  
tel: 44.118.923.0800  
fax: 44.118.923.0801

**Asia**

**Asia Regional Office**  
#05-02A/03 New Tech Park  
151 Lorong Chuan  
Singapore 556741  
tel: 65.6303.2100  
fax: 65.6303.2199

**Australia**

Level 4, 1-3 Atchison Street  
St. Leonards, NSW 2065  
Australia  
tel: 61.2.9330.4400  
fax: 61.2.9437.0204

**South America & Mexico**

**Intermec South America Ltda.**  
Rua Samuel Morse 120 9 andar  
Brooklin CEP04576-060  
São Paulo, SP  
Brazil  
tel: 55.11.5502.6770

**Intermec Technologies de Mexico**  
Av Tamaulipas #141, Primer Piso  
Col. Hipodromo Condesa

**Internet**

www.intermec.com

**Sales**

800.934.3163  
(toll free in N.A.)  
tel: 425.348.2726

**OEM Sales**

tel: 425.348.2762

**Customer Service and  
Support**

800.755.5505  
(toll free in N.A.)  
tel: 425.356.1799

Copyright © 2006 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611793-01A 12/06

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

**China & Hong Kong****Guangzhou**

Tel: 86 - 20 - 2882 1366

Fax: 86 - 20 - 8761 0213

GZ\_Sales@sysscan.com.hk

**Shanghai**

Tel: 86 - 21 - 6282 5319

Fax: 86 - 21 - 6282 5283

SH\_Sales@sysscan.com.hk

**Hong Kong**

Tel: 852 - 2370 2227

Fax: 852 - 2370 2054

HK\_Sales@sysscan.com.hk

<http://www.sysscan.com.hk> <http://www.sysscan.com.cn>