

M71 数字键盘PDA



■ 通讯性能

- | 4G全网通LTE，网络无死角
- | 802.11ac/a/b/g/n企业级独立Wi-Fi
- | 蓝牙4.0，低功耗，远距离，完美匹配无线打印机

■ 扫描性能

- | 全新一代全球最薄高性能二维影像扫描头
- | 支持VGA和百万像素版本
- | 采用Datalogic解码技术和算法授权

■ 工业防护

- | IP65工业防护等级
- | 电池触点铡刀式设计，摔落和翻转冲击时不断电
- | 结构板槽型结构固定电池，确保整体机身最轻薄

■ 独有产品特性

- | 最新一代4核2GHz处理器，长寿命供应周期
- | 支持安卓9和安卓10升级
- | 支持最多10个条码同时读取
- | 大容量电池配合超低功耗，实现3小时快充，15小时超长工作时长，50天待机
- | 免费APPLOCK、Easy Deploy等系统管理软件，确保高效管理及部署

应用领域



制造业



仓储物流



公共事业



零售业



医疗设备集成



移动支付

China & Hong Kong

M71 Specifications

OS	Android 9
CPU	2GHz, Quad/Octa Core, 12nm
MEMORY	2+16/3+32
Extend Slot	MicroSD, support SDHC, up to 64GB; One micro SIM connector
PC Communication	USB 2.0 OTG : Type-C: Support TYPE-C Headset
Sensors	Light, Proximity, 3D G sensor, Hall
LED	Charging, Scan and System status
Charging Time	<3.5 hours(Room Temperature) <4 hours(35 ℃)
Operation Duration	14 hours
Data Collection	
Scan Engine	Mobydata E3200-LE/E3250-LE
2D	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode;
	Micro QR Code; QR Code; EAN/JAN Composites; GS1 DataBar Composites;
	GS1 DataBar Expanded Stacked; GS1 DataBar Stacked;
	GS1 DataBar Stacked Omnidirectional; MicroPDF417; PDF417; UPC A/E Composites
1D	Auto discriminates all standard 1D codes including GS1 DataBar™ linear codes.
Post	Australian Post; British Post; China Post; IMB; Japanese
	Post; KIX Post; Korea Post; Planet Code; Postnet; Royal
	Mail Code (RM4SCC)
NFC(Optional)	13.56MHz NFC
Wireless Connectivity	
WLAN	802.11 ac/a/b/g/n
WWAN	TDD-LTE (B38/B39/B40/B41)
	FDD-LTE (B1/B3/B7)
	UMTS/HSDPA/HSPA/HSPA+ (900/2100 MHz)
	GSM/EDGE/GPRS (900/1800MHz)
VoLTE	LTE CAT6
CA	Downlink 300Mbps, B1/B3/B7/B40/B41
WPAN	BT 4.2/BLE
GPS	GPS/A-GPS, GLONASS, Beidou ,Galileo

Physical Specifications	
LCD	4 inch, 800*480, visible under sunshine
Touch	GFF Captive Touch, Dragontrail Glass
Camera	Auto focus 8Mega, with flash LED
Keypad	24 Numeric Keypad
	Left/Right Scan Key, Left/Right K1,K2 user-defined Key
	Back, HOME, Switch
Receiver	Support
Speaker	Min 90db at 10cm-1KHz Voice
Mic	Noise Reduction Mic
Charging IO	USB type-C,
	Charging Pad
Battery	Removable 3800mAh-4000mAh
Dimension	160*71*17mm
Weight	269g
Environmental Specifications	
Operation	-20°C ~ +50°C
Storage Temperature	-30°C ~ +70°C
Humidity	10% ~ 90%
Drop	1.5m, concrete, 12 drops
Tumble	600hits, 0.5m, Steel
IP	IP65
ESD	±8kV Contact, ±15kV Air
Keypad lifecycle	300K
Accessories	
Charging Cradle	Support 1 device and 1 battery
Handstrap	Black, Nylon
Battery	Removable 3800mAh-4000mAh
Gift Box	Handstrap, 5V 2A wall adapter, Type-c USB cable, QSG, Battery
Device, Battery, QSG, Adapter, USB cable.	



China & Hong Kong

Hong Kong
Tel: 852 - 2370 2227
Fax: 852 - 2370 2054

Guangzhou
Tel: 86 - 20 - 2882 1366
Fax: 86 - 20 - 8761 0213

Shanghai
Tel: 86 - 21 - 6282 5319
Fax: 86 - 21 - 6282 5283

HK_Sales@sysscan.com.hk GZ_Sales@sysscan.com.hk SH_Sales@sysscan.com.hk

<http://www.sysscan.com.hk> <http://www.sysscan.com.cn>