

# QuickScan<sup>®</sup> QS2500

Linear Imager Handheld Scanner



#### Ideal for:

- Retail applications
- Health care
- Inventory
- Office automation
- Document tracking
- Light industrial

#### Features:

- Aggressive reading and an extended depth-of-field
- Reads Reduced Space Symbology (RSS), PDF417 and linear codes for flexibility
- Ergonomic "aim and shoot" design
- Reliable and durable, providing long lasting performance

#### Performance That You Expect From PSC

The QuickScan<sup>®</sup> QS2500 Linear Imager Handheld Scanner is the newest member of the QuickScan<sup>®</sup> product family. For retail, office, and light-industrial applications, the QS2500's 200 scans-per-second linear imager scan engine provides snappy reading performance and an extended depth-of-field. And the QS2500 also reads poorly printed bar code labels quickly and easily.

#### Loaded with Features for Today and Tomorrow

The QS2500 is capable of reading a wide range of bar code symbologies, including Reduced Space Symbology (RSS) and PDF417, allowing you flexibility in reading now and in the future. It also features flash memory for easy software upgrades, along with programming and label editing. Its enclosure is lightweight and ergonomic, and a hands-free tabletop stand is available.

#### Outstanding Durability and Reliability

The QS2500's Linear Imager scan engine has no moving parts and will reliably read for years to come. It withstands 5' / 1.5 m drops to concrete and has an IP42 sealing rating to protect it in most indoor applications. In addition, the QS2500 utilizes the same high-quality interface cables shared by other PSC handhelds, including the rugged PowerScan<sup>™</sup> industrial handheld scanner. And the QS2500 is backed by PSC's three-year factory warranty on the scanner and a one-year warranty on PSC interface cables.

#### Exceptional Value

The QS2500 is loaded with performance, features and reliability, all at a surprisingly low price. Its three-year warranty and low purchase price minimize your cost of ownership. The QS2500 is an exceptional value!



# Specifications

## QS2500

### Mechanical

- Length: 4.5" (11.4 cm)
- Width: 2.9" (7.4 cm)
- Height: 7.3" (18.5 cm)
- Weight: 6.3 oz. (179 g), cable not included

### Optical

- Light source: 660 nm Visible Red Diode
- Scan rate: 200 scans/sec.
- Scan width: 4.0" (10.2 cm) at 5.0" (12.7 cm) from the label
- Depth-of-Field: Refer to chart below
- Resolution: 5 mils (0.13 mm)
- Print contrast ratio: 25% or higher
- Pitch:  $\pm 60^\circ$
- Skew:  $\pm 75^\circ$
- Scan angle:  $46^\circ$
- Ambient light immunity
  - Artificial & Sunlight: 6,968 foot-candle (75,000 Lux)

### Electrical

- Operating current
  - Operating: 225 mA @ 5 VDC
  - Standby: 100 mA @ 5 VDC

### Environmental

- Temperature
  - Operating: 32° to 113° F (0° to 45° C)
  - Storage: -22° to 149° F (-30° to 65° C)
- Humidity: 5 to 95% NC
- Shock: Withstands ten 5.0' (1.5 m) drops onto concrete
- Physical shock: 1500 g, 1 ms
- Water & Dust: Resistant, IEC 60529 rating IP42DW
- ESD protection: Functional after 15kV discharge

### Communications

- RS-232
- Keyboard Wedge/Wand Emulation
- USB
- IBM 46XX
- IBM USB

### Decoding Capability – Autodiscriminates

- UPCA, E / EAN 8,13 / JAN 8,13 (including add-ons P2 / P5, Code 128)
- Code 128
- Pharmacode 39
- Codabar
- Industrial 2 of 5
- RSS 14
- RSS Expanded
- MSI/Plessey
- Telepen
- Code 11
- Code 93
- Code 39
- Interleaved 2 of 5
- Matrix 2 of 5
- RSS-14 Stacked
- RSS Limited
- UK/Plessey
- Code 16K
- PDF417 w/audio assist

### Safety & Regulatory

- Electrical: Complies to: Gost R; TÜV; UL; cUL
- Emissions: Complies to: FCC-A; EN 55022-B; BCIQ CNS 13438; AS/NZS 3548; VCCI-B

Depth-of-Field	
Printing resolution, contrast and ambient light dependent	
Label Density	Range
5 mils	1.0" to 4.5" / 2.5 to 11.4 cm
10 mils	0.5" to 8.5" / 1.3 to 21.6 cm
13 mils	0.5" to 11.0" / 1.3 to 28.0 cm
20 mils	1.0" to 16.0" / 2.5 to 40.6 cm
40 mils	2.0" to 28.0" / 5.0 to 71.0 cm



This product is manufactured in Taiwan.



Gooseneck Tabletop Stand  
P/N: 8-0591



Hong Kong  
Tel: 852-23702227  
Fax: 852-23702054  
sales@sysscan.com.hk

**China & Hong Kong**  
Guangzhou  
Tel: 86-20-87591553  
Fax: 86-20-87598472  
gz\_sales@sysscan.com.hk

Shanghai  
Tel: 86-21-62825319  
Fax: 86-21-62825283  
sh\_sales@sysscan.com.hk

[www.sysscan.com.hk](http://www.sysscan.com.hk) or [www.sysscan.com.cn](http://www.sysscan.com.cn)

