

## Takame F880BT Scanner

Aware of the AIDC market always calls for continuous technological advancement and enhancement to meet the evolvement of global economy, Takame F880BT bar code laser imager is built specifically to fill this requirement by combining the benefits of imaging technology with laser aimer, delivering ultimate cost performance and lower total cost of ownership.

### Quick and easy barcode capture:

Integrated with laser aimer, F880BT projects sharp laser aiming without diverging and spreading out. This enables it to decode barcodes intuitively and easily in any lighting condition, from the low ambient light environments to direct sunlight.

### Superior wireless connectivity:

F880BT provides several radio link modes to communicate with most host devices. When Bluetooth-enabled host device is not available, it can work with the smart cradle in PAIR mode or PICO mode. This provides an instant plug-and-play cordless migration to your existing non-Bluetooth-enabled IT assets. Moreover, the PICO mode supports multiple connections up to 7 scanners with one smart cradle, reducing your total cost of ownership.

### All-around functionality for diverse App:

When enabling Batch Scanning function, F880BT is capable of collecting more than 20,000 EAN-13 barcode data. This makes F880BT ideal for inventory application. The Out-of-range scanning feature allows F880BT to continue scanning data even when it loses radio connection. Once you enable the Presentation Scanning Auto-sense function for hand-free application.



Sharp laser aiming for quick and precise barcode capture in any lighting condition

### All-in-one interface

Including USB HID, UFB COM, PS/2 keyboard wedge and RS232

### Code Support

Gs1 databar Linear-stacked, PDF, MicroPDF and composite code

### Support multiple connections

Up to 7 scanners in PICO mode

# Specifications

## Performance Characteristics

Optical System	High performance Linear Imaging Engine
Print Contrast	30% minimum reflective difference
Minimum Resolution	Typical 3 mil (Code 39, PCS 0.9)
Working Distance <sup>1</sup>	More than 16 inches on 100% UPC/EAN symbols More than 24 inches on 20 mil Code 39
Light Source	630nm visible red LED with laser aiming
Scan Rate	Dynamic scanning rate up to 500 scans per second
Reading Direction	Bi-directional (forward and backward)
Pitch/Skew/Tilt	± 65° / ± 65° / ± 55°
Operating Modes	Trigger, Presentation
Configuration Setup	Bar code command Windows utility - FuzzyScan PowerTool
Data Editing	Condensed DataWizard via bar code command Full-feature DataWizard via FuzzyScan PowerTool
User Interfaces	Blue link indicator and 2-color status indicator Programmable beeper Optional vibrator

## Electrical Characteristics

Battery	3.7V, 2200mAh Li-ion rechargeable battery	
Battery Charge Time	Approx. 4-5 hours per full charge	
Scans per full Charge <sup>2</sup>	More than 45,000 scans and transmissions	
Voltage & Current (Scanner and Cradle)	Voltage 5 ± 10% VDC	Current (Charging/ Non Charging) Max.680 mA / 85mA with external power

## Communication Characteristics

RF Standard	Bluetooth v2.1 EDR
RF Frequency	Band 2.402~2.4830 GHz unlicensed ISM band
Radio Link Modes	PAIR mode, PICO mode, SPP mode, HID mode
Communication Range	More than 80 meters in open space when working with smart cradle, line of sight
Supported Profiles	SPP, HID

## Supported Symbolologies

1D Linear (F880BT)	Code 39, Code 39 Full ASCII, Code 32, Code 39 Trioptic Code 128, UCC/EAN-128, Codabar, Code 11, Code 93 Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5 German Postal Code, China Postal Code, IATA UPC/EAN/JAN, UPC/EAN/JAN with Addendum Telepen, MSI/Plessey & UK/Plessey GS1 DataBar (formly RSS) Linear & Linear Stacked
Linear-stacked (F880BT)	PDF417, Micro PDF417, Codablock, Composite (available for F880BT only)

## User Environment

Drop Specifications	Withstand multiple 1.5m/5ft. drops to concrete
Environmental Sealing	IP41
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Humidity	5% to 95% related humidity, non-condensing
Ambient Light Immunity	0 ~ 100,000 lux
ESD Protection	Functional after 15kV discharge

## Physical Characteristics

Dimension	97.0 mm (L) x 65.0 mm (W) x 156 mm (D) 3.81 in. (L) x 2.55 in. (W) x 6.14 in. (D)
Weight	198g (battery included)
Color	Light Gray or Black

## Safety & Regulatory

EMI/RFI	FCC Part 15 Class B, Taiwan EMC (BSMI) European Union EMC Directive (CE)
Radio	FCC Part 15 Subpart C, Japan MIC T401 CE EN300 328, Taiwan LP0002 (NCC)
Safety <sup>3</sup>	LED Eye Safety IEC60825-1, EN60825-1 Laser Eye Safety IEC60825-1, Class 1
Environmental	Compliant with RoHS directive

## Accessories

Smart Cradle	RF Standard : Bluetooth v2.1 EDR Battery charging : Fast charge User Interfaces : 1 blue link indicator 2-color status indicator Beeper, Paging/Reset button Host Interface : PS/2 (DOS V) Keyboard Wedge, TTL RS232 Serial, USB HID, USB COM
Charging Cradle	Battery charging : Fast charge User Interface : 1 blue power indicator
Interface Cables	PS/2 (DOS V) Keyboard Wedge Cable RS232 Serial Cable USB Cable
Others	5VDC Power Supply Unit Hand-Free SmartStand Universal Holder

1. The working distances are measured in 400lux office environment using Grade A bar codes.
2. The number of scans per full charge is measured under factory preset test condition.
3. Don't stare into the Laser beam.